[/lommy pro T]

Quick Start Guide Lommy Pro T

Congratulations on your new Lommy Pro T

This guide will give you a short introduction to the functions and fitting of the unit.



- 1. Hole for mounting
- 2. On/off button
- 3. Light indicator showing the status of the Lommy
- 4. USB-port for charging
- 5. Connection to installation kit



For technical questions, please contact Flextrack Support: support@flextrack.dk



Getting started

Use the diagram below as a guide for installing your Lommy Pro T. As a standard, the cables and installation kit are enclosed with your Lommy Pro T and will be there when you receive it.

In order to turn the unit on, briefly press the on/off button. To turn off the unit, press the on/off button for 5 seconds until the yellow LED starts blinking fast. Release the button for less than 2 seconds before pressing it briefly again, after which the Lommy Pro T will switch off.

Installation	A 1A fuse should be fitted close to the battery!		
	White. Connect to battery +		
	Black. Connect to ground/battery -		
	Brown. Input 1. Has to be connected to "+" at ignition		
	Grey. Input 2 (extra equipment)		
	Blue. Output 1 (extra equipment)		

The placement of your Lommy Pro T

The technology in the unit relies on GSM communication and GPS postioning via internal antennas. Materials like concrete and most metals will dampen the GSM/GPS signals significantly, and placement behind such materials should be avoided.

On the other hand, the signal can pass through materials like plastic, glass fiber, wood and glass of moderate thickness.

Note: Some windshields can contain a thin coating of metal oxide, that will weaken or hinder the signal.

Examples of good placements in the car:

- Directly under the outside of the dashboard
- The center console, between the front seats
- The top of the back seat's backrest
- Under the rear shelf, if this isn't made of metal

When a location has been chosen, it is highly recommended to do a test run, where the performance under real working conditions is observed over a suitable time span.



Setting up and monitoring your Lommy Pro T via your computer or portable unit



If you have a subscription with Flextrack, then you can log in at www.flextrack.dk to set up and change the configuration and alarm destinations. Your username and password are the 10-digit serial number found on the back of your Lommy Pro T.

When you're logged into the website, you can see the status and position of your Lommy Pro II, as well as a range of other useful information.

If your vehicle or another possession is stolen, you can use this function to tell the police where it's been and where it is now, so you can get it back.

Light indicators (LEDs) on the front of the device

Light colour	Green	Red	Blue	Yellow
Name	GSM	CHG	GPS	SYS
Blinking patterns	Blinks sporadically: OK	2 short blinks: Charging	One blink: No GPS signal	2 short blinks: Connected to the Internet
Continuous light		Fully charged		ls in the process of starting up, or is low on battery
Others	Blinking continuously: Problem with the SIM card	Blinking slowly: Switching off due to low power	Several blinks: GPS is connected. The number of blinks = the number of satellites connected	One blink: No connection to the server

For technical questions, please contact Flextrack Support: support@flextrack.dk



Flextrack, Høgevej 19, DK-6705 Esbjerg Ø, Denmark

[version 1.0]